



GRIT SIZES RECOMMENDATIONS

	Power Tools		Hand Tools	Floor Tools
Materials examples:	Angle Grinder or slow turning machines	with Velcro		
Laminates	24-36	36-240	36-240	80-120-180-240
Fibre glass	14-24-36	36-240	24-240	24-36-60
Fibre reinforced materials	24-36	60-240	60-240	
Kevlar	36	80-240	80-240	
Bricks	14-24-36	36-60	24-36	24-36-60
Concrete	24-36	36	24-240	14-24-36
Filler	14-24-36	14-240	14-240	14-24-36
Sandstone	24-36	36-240	36-240	24-36-60
Ceramic Tile	24	60-240	24-60	
Marble	24-36-60	120-240	120-240	24-36-60
Slate	24-36	60-240	60-240	
Terrazzo	24-36	120-240	120-240	24-36
Composites / PVC	6-10-14-24-36	80-240	80-240	36-60-80
Glue both soft and hard	24-36	36-80	24-36	6-10-14
Carpet backing	14	24	24	6-10-14
Rust	14	36-120	24-240	24-36-60
Moulding sand	14-24	24-60	24-60	
Plaster of Paris	14-24-36	60-240	60-240	14-24-36-60
Paint	14-36	60-240	60-240	14-24
EPOXY	24-36	24-36	24-36	3-6-10-14-24
Insulation materail	14	14	24	10-14
Hard and soft wood	14-24	80-240	80-240	36-60-80-120-180-240
Stone	36-60		24-36-60-80	24-36-60

Feel free to contact us if you need advise choosing the right grit size

www.carbide.dk